

CB2600-86

## CONE BOTTOM BULK STORAGE TANKS

CB1000-64  
w/CB064-45ST

Cone Bottom Tanks are selected when a more complete drain out of stored chemical is required in indoor or outdoor installations. Tanks require stands to support the conical bottoms. Tanks are manufactured from medium- or high-density polyethylene with U.V. inhibitors and designed for containment of liquids of up to 1.7 specific gravity. Tank walls are translucent for level viewing and equipped with gallon indicators.

CB1700-86 w/CB086-15ST


CB0200-42  
w/CB042-45ST

PART NO.	CAPACITY	SPECIFIC GRAVITY	WEIGHT	TANK DIMENSIONS (diameter x height)	OVERALL HEIGHT (including stand)	LID	FITTING
CB0150-36	150 Gallon-45 deg	2.0	61	36 x 51	63"	12"	2"
CB0200-42	200 Gallon-45 deg	2.0	75	42 x 55	65"	12"	2"
CB0300-42	300 Gallon-45 deg	2.0	100	42 x 67	76"	16"	2"
CB0345-52	345 Gallon-45 deg	2.0	100	52 x 58	70"	12"	2"
CB0350-42	350 Gallon-45 deg	2.0	118	42 x 81	93"	12"	2"
CB0500-52	500 Gallon-45 deg	2.0	130	52 x 81	92"	12"	2"
CB1000-64	1000 Gallon-45 deg	1.7	250	64 x 98	112"	16"	2"
CB1000-90	1000 Gallon-15 deg	1.7	210	90 x 54	64"	16"	2"
CB1200-90	1200 Gallon-15 deg	1.7	240	90 x 62	74"	16"	2"
CB1300-90	1300 Gallon-15 deg	1.7	260	90 x 65	75"	16"	2"
CB1490-64	1490 Gallon-45 deg	1.7	340	64 x 132	146"	16"	2"
CB1600-90	1600 Gallon-30 deg	1.7	284	90 x 85	93"	16"	2"
CB1700-86	1700 Gallon-15 deg	1.7	284	86 x 85	96"	16"	2"
CB2500-90	2500 Gallon-15 deg	1.7	435	90 x 111	121"	16"	2"
CB2600-90	2600 Gallon-30 deg	1.7	500	90 x 123	129"	16"	2"
CB2600-86	2600 Gallon-45 deg	1.7	500	86 x 146	154"	16"	2"
CB3000-90	3000 Gallon-15 deg	1.7	550	90 x 128	137"	16"	2"
CB4600-102*	4600 Gallon-15 deg	1.7	1200	102 x 155	166"	16"	2"
CB4900-102*	4900 Gallon-15 deg	1.7	1300	102 x 159	170"	16"	2"
CB6900-122**	6900 Gallon-15 deg	1.7	1700	122 x 168	177"	16"	2"
CB8250-122**	8250 Gallon-15 deg	1.7	2100	122 x 195	205"	16"	2"

\* indicates heavy duty fitting \* indicates available with 3" fitting

## CONE BOTTOM STANDS

PART NO.	CAPACITY	WEIGHT	CLEARANCE (from tank to ground)
CB036-45ST	150 Gal-45 deg	63	12"
CB042-45ST	200, 300 or 350 Gal-45 deg	82	11"
CB052-45ST	345 or 500 Gal-45 deg	174	13"
CB064-45ST	1000 or 1490 Gal-45 deg	320	14"
CB086-15ST	1700 Gal-15 deg	360	11"
CB086-45ST	2600 Gal-45 deg	580	12"
CB090-15ST	1000, 1200, 1300, 2500 or 3000 Gal-15 deg	380	11"
CB090-30ST	1600 or 2600 Gal-30 deg	640	9"
CB102-15ST	4600 or 4900 Gal-15 deg	448	11"
CB122-15ST	6900 or 8250 Gal-15 deg	1020	10"

CB086-45ST  
Fluid View  
Feature