



TRACTOR MOUNTED TANKS

Tractor Mounted Tanks are designed as portable (non DOT approved) applicator tanks. Tanks require the bottom to be fully supported with a cradle for use. Gallon indicators are included and the tank walls are translucent for level viewing. Ends of tanks feature fitting flats to facilitate a variety of installation options. Bottom of tanks feature a collection sump for full drain out. Tanks are manufactured from medium-density polyethylene with U.V. inhibitors and designed for containment of liquids of up to 1.7 specific gravity.

OVAL TANKS

PART NO.	CAPACITY	WEIGHT	DIMENSIONS (width x length x height)	LID	FITTING
OT0300-31	300 Gallon Oval	100	31 x 49 x 56	16"	3/4" & 1-1/4"

TEAR DROP TANKS

PART NO.	CAPACITY	WEIGHT	DIMENSIONS (width x length x height)	LID	FITTING
TD0250-36	250 Gallon	97	36 x 52 x 45	12"	3/4" & 1-1/4"
TD0300-36	300 Gallon	109	36 x 62 x 45	12"	3/4" & 1-1/4"



CRADLES

PART NO.	CAPACITY	WEIGHT	BANDS
TD0250-C	250 Gallon	96	2.5" x 74.5"
TD0300-C	300 Gallon	108	2.5" x 74.5"

CUT-AWAY APPLICATOR TANKS

PART NO.	CAPACITY	WEIGHT	DIMENSIONS (width x length x height)	LID	FITTING
CAW0200-24	200 Gallon	80	24 x 55 x 46	8"	3/4" & 1-1/4"
CAW0250-24	250 Gallon	95	24 x 61 x 51	8"	3/4" & 1-1/4"

CUT-AWAY CRADLES

PART NO.	CAPACITY	WEIGHT	BANDS
CAW0200-C	200 Gallon	135	3" x 60"; 3" x 40"
CAW0250-C	250 Gallon	143	3" x 72"; 3" x 51"

CAW0250-24/CAW0250-C

